

JADE ZOOM



The Jade Zoom is a versatile and powerful LED lighting fixture. With a zoom range from 9° to 58° (Bridgelux) or 11° to 67° (Xicato), it is ideal for museum, gallery, or high-end retail lighting. The advanced optical system ensures uniform light quality, while the choice of LED light sources allows for a perfect fit to the lighting plan.

Categories: [Jade Series](#), [Indoor](#), [Track fixtures](#), [Museums & Galleries](#)

> Specifications

Type	Jade Zoom, 25 or 35 Watt track or surface mounted spot
Colour	Black, white or grey
Material	Anodized or coated aluminium & PC/ABS V0
Weight	955 gram
Swivel	340° horizontal 350° vertical

Optics	9°- 58° 11°- 67°
Light source	Bridgelux or Xicato
Light output	1500 - 2000 lumen
CRI	>92 or >97
LED colours	2700K 3000K 3500K 4000K

Power consumption	Max. 25 - 35 Watt
Power supply	180~264 VAC
Driver	Driver included Driver internal
Dimming	Local dim DALI Casambi DMX512 Wireless DMX
Connection	Track adapter, Global or Eutrac

IP rating	IP 20
Protection class	1
Certifications	CE

Lifetime	50.000h
LB Value	L90B10 at 50.000h


Warranty 5 years

Accessories


A customizable snoot that can be build up in segments of 2 cm. Rotatable barndoor, Beam shapers and Honeycomb louvre.

Remarks

The beam angle can be adjusted from the backside of the fixture.



Jade C



Jade B

