

2.50 mm² Speaker Cables with Flame Resistant Jacket

Item Code: 1E00193

CVS LK02N25

GENERAL DATA

Application	Mobile
Cable O.D. (mm)	9.2
Bending Radius	10 x O.D.
Min Operating Temperature (°C)	-20
Max Operating Temperature (°C)	70
Standard Reels (m)	100
Reel Material	Cardboard
Weight (Kg/100m)	13.00
Jacket Color	Black
Jacket Material	PVC TM2
Jacket Nominal Thickness (mm)	1.2

ELECTRICAL DATA

Max Conductor DCR (ohm/km)	7.98
Mutual Capacitance (pF/m)	110
Rated Voltage (Vac)	300
Test Voltage (Vac)	2000

CONDUCTOR

Conductors Quantity	2
Conductor Strands	80
Conductor Strands O.D. (mm)	0.193
Conductor Area (mm ²)	2.5
Conductor Material	Flexible electrolytic bare copper
Conductor Insulation O.D. (mm)	3.4
Conductor Insulation Thickness (mm)	0.7
Conductor Insulation Material	PVC R2

ADDITIONAL INFORMATION

Standard reference	IEC 60332-1-2
	IEC 60332-3-24 Cat.C
	EN 50363-3