





CYNAP PURE MINI

COMPACT, WIRELESS PRESENTATION SYSTEM

NO APPS, NO DONGLES, NO CABLES!

Cynap Pure Mini is a simple yet versatile wireless presentation device. Ideal for small meeting rooms, huddle spaces, and classrooms. It allows users to share content onscreen from any device without using cables or additional software.

KEY FEATURES



BYOD - Wireless Screen Sharing

Support for AirPlay, Miracast, and Chromecast for app-free, dongle-free screen mirroring from any device.



4K Output Resolution

Provides sharp and clear 4K UHD output, ensuring high-quality visuals for presentations - Up to 4 wireless connections simultaneously.



Maximum Ease of Use

Intuitive operation eliminates the need for training, enabling users to connect and present quickly and easily.



Enterprise Level Security

Linux system with wireless data encryption, user access management, and customizable security features to meet the needs of every organization.



Remote Management & Administration

vSolution Link Pro - free-of-charge software for easy remote setup and maintenance.

ADDITIONAL FUNCTIONS



Flexible Network Integration



Room Management APIs



Touchback Function



Bluetooth Device Discovery



Up to 5 Years Warranty



Audio USB Input



Peripheral Device Control



Free Firmware Updates



TECHNICAL SPECIFICATIONS

CYNAP PURE MINI

Operating system	Linux
Output resolution	2160p60/30, 1080p60/30, 720p60
Supported devices for wireless mirroring (up to 4K depending on device)	iOS, iPadOS, Android, Windows, macOS, Chrome OS
Supported mirroring protocols	AirPlay, Miracast (Peer-to-Peer and MICE), Chromecast, vSolution Cast
Max. no. of on-screen windows	4
Protected/Open presentation modes	Yes
vSolution Link Pro remote admin software	On premise
Peripheral device control	Yes
Video output	HDMI x1
Audio	HDMI out, USB Out
USB port	Front: 1x USB 3.0, 1x USB 2.0
LAN port	Yes, 1x 1GigE
Bluetooth device discovery	Yes
WLAN standards (Wi-Fi 5)	2.4 GHz in Access Point Mode / 2.4 and 5 GHz in Infrastructure Mode
Network protocols	TCP/IP, HTTP, HTTPS, SNTP/NTP, SSL, SSH, UDP
IP configuration	DHCP, Static (IP address, Subnet mask, Default gateway, DNS server), Proxy, Interface priority
Security authentication for LAN	IEEE 802.1X
Security encryption for wireless WLAN	WEP, WPA2, WPA2 Enterprise or IEEE 802.1X
RMS encryption / RMS APIs	Yes / Customisable demo modules available
External controlling	Multi-touch display, web interface, room control system, keyboard / mouse, optional remote control, vSolution App
Dimensions (L x W x H)	70 x 70 x 35 mm (2.76 x 2.76 x 1.37")
Power consumption	24W
Weight	260g (0.57lb)
Optional accessories	Optional remote control
Included accessories	Power supply, VESA mount (75mm /100mm)
Free firmware updates / no license fees	Yes
Limited warranty	3 years (optional extension to 5 years)
	Design and specifications subject to change

Design and specifications subject to change!